

## Description

Distribution and trunk coaxial cable for burial installation - 75 Ohm  
Underground installation cable (Screening Class A)

Coaxial Cables

CAVEL®

since 1968

## Data Sheet

CATV11



Ø	1,63	7,20	7,37	7,85		10,10
	(Cu)	(PEG)	(Al/Pet/Al/Sur)	(CuSn)	(Jelly2)	(PE)

## Standards

EN 50117-2-3

## Construction data

Inner conductor of plain copper		(Cu)	Ø 1,63 ± 0,03	mm
Dielectric of physical foam polyethylene	0,03	(PEG)	Ø 7,20 ± 0,10	mm
Aluminium/Polyester/Aluminium/Surlyne tape longitudinally overlapped and bonded to the dielectric		(Al/Pet/Al/Sur)		
Braid of tinned copper wires		(CuSn)		
Braid optical coverage (IEC 96-1)			63	%
Tracer Identifier		Year + Flag		
Water repellent sealing (sheath)		(Jelly2)		
Diameter under Sheath			7,85	mm
Outer sheath of Polyethylene - black - with carbonblack		(PE)	Ø 10,10 ± 0,15	mm
Printed each meter by yellow ink-jet :				

**CAVEL CATV 11 MADE IN ITALY 75 Ohm EN50117-2-3 CEI-UNEL 36762 C-4 (U0 =400V) ss/aa m**

(ss=week, aa=year) (m=meter marking)

## Physical data

Weight of copper conductors		34,57	kg/km
Total weight of cable		85,65	kg/km
Minimum bending radius (single/repeated bending)		100	mm
Maximum cable pulling strength		300	N
Fire Load	2.140	MJ/km	594 kWh/km

## Electrical data

Characteristic impedance	200 MHz	75 ± 2	Ohm
Capacitance (@1kHz)		52 ± 2	pF/m
Velocity Ratio		85 %	
Inner conductor resistance		8,50	Ohm/km
Outer conductor resistance		10	Ohm/km
Loop resistance		18,50	Ohm/km
Sheat Insulation voltage (spark test)		8	kV
Maximum current (Ieff)		16	A
Structural return loss (SRL)			
5 - 470 MHz	>30 dB		
470 - 1000 MHz	>28 dB		
1000 - 2000 MHz	>23 dB		
2000 - 3000 MHz	>20 dB		

## ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli  
Tel +39-382.815150 Fax +39-0382.814212

## Date

29/02/2016

## Responsible

PierPaolo Piccinini

**Description**

Distribution and trunk coaxial cable for burial installation - 75 Ohm  
 Underground installation cable (Screening Class A)



Data Sheet

**CATV11**

Screening Attenuation (SA)	SA-Class A	Shield Transfer Impedance (Zt)	Zt-Class B
30 - 1000 MHz	>85 dB	5 - 30 MHz	< 8 mΩ/m
1000 - 2000 MHz	>95 dB		
2000 - 3000 MHz	>95 dB		


Attenuation (at 20°C )

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	1,10	862	11,90
10	1,50	1000	12,80
30	2,20	1750	17,90
50	2,80	2150	19,80
200	5,60	2400	21,00
300	6,90	3000	24,00
470	8,80		

**Attenuazione di schermatura / Screening Attenuation**

**Cavo classe A / A Class Cable**

Cavo tipo / Cable type: CATV11



**Connectors**

- FA17/73** Serie F Twist-On, F Twist-On, for indoor installation, nitin-plated brass - 33,0 mm x 14,5 mm
- F163** Series F Crimp, F Crimp, for indoor installation, nitin-plated brass - 35,0 mm x 14,0 mm
- FC11QM** Series F Compression, Quick Mount, for outdoor installation
- FM-32** Series F, male, for outdoor and underground installation, nitin-plated brass - 76,0 mm x 31,0 mm
- IEC14M-32** Series IEC (no tool), male, for outdoor and underground installation, nitin-plated brass - 64,5 mm x 21,0 mm
- NM-32** Serie N, male, for outdoor and underground installation, nitin-plated brass - 62,5 mm x 21,0 mm

**ITALIANA CONDUTTORI s.r.l.**

Viale Zanotti 90 I - 27027 Gropello Cairoli  
 Tel +39-382.815150 Fax +39-0382.814212

Date

29/02/2016

Responsible

PierPaolo Piccinini

**Description**

Distribution and trunk coaxial cable for burial installation - 75 Ohm

Underground installation cable (Screening Class A)

**Data Sheet****CATV11****↑↑↑ Connectors**

- 5/8MU-32** Serie 5/8", male, for outdoor and underground installation, nitin-plated brass - 69,0 mm x 20,5 mm
- 3,5/12M-32** Serie 3,5/12", male, for outdoor and underground installation, nitin-plated brass - 65,5 mm x 24,5 mm

**ITALIANA CONDUTTORI s.r.l.**Viale Zanotti 90 I - 27027 Gropello Cairoli  
Tel +39-382.815150 Fax +39-0382.814212

Date

**29/02/2016**

Responsible

**PierPaolo Piccinini**