


Description

Triple shielded coaxial cable for Broadband Distribution Networks
75 Ohm
Triple shielded cable (Screening Class A++)



Data Sheet

TS11J



Standards

EN 50117-2-3

Construction data

Inner conductor of plain copper	(Cu)	Ø 1,63 ± 0,03	mm
Dielectric of physical foam polyethylene	0,03 (PEG)	Ø 7,20 ± 0,10	mm
Aluminium/Polyester/Aluminium/Surlyne tape longitudinally overlapped and bonded to the dielectric	(Al/Pet/Al/Sur)		
Braid of tinned copper wires	(CuSn)		
Braid optical coverage (IEC 96-1)		63	%
Tracer Identifier	Year + Flag		
Aluminium/Polyester j-fold and longitudinally overlapped	(Al/Pet J-foil)	32+3 x 30/19	mm/µm
Diameter under Sheath		7,97	mm
Outer sheath of Polyethylene - black with two green bands - with carbonblack	(PE)	Ø 10,30 ± 0,20	mm

Printed each meter by yellow ink-jet :

CAVEL TS 11 J MADE IN ITALY 75 Ohm EN50117-2-3 Class A++ CEI-UNEL 36762 C-4 (U0 =400V) * LTE PROTECTION * ss/aa m

(ss=week, aa=year) (m=meter marking)

Physical data

Weight of copper conductors		34,57	kg/km
Total weight of cable		86,70	kg/km
Minimum bending radius (single/repeated bending)		100	mm
Maximum cable pulling strength		300	N
Fire Load	2.083 MJ/km	579	kWh/km

Electrical data

Characteristic impedance	200 MHz	75 ± 2	Ohm
Capacitance (@1kHz)		52 ± 2	pF/m
Velocity Ratio		85 %	
Inner conductor resistance		8,50	Ohm/km
Outer conductor resistance		7,50	Ohm/km
Loop resistance		16	Ohm/km
Sheat Insulation voltage (spark test)		8	kV
Maximum current (I _{eff})		16	A
Structural return loss (SRL)			
5 - 470 MHz	>30 dB		
470 - 1000 MHz	>28 dB		
1000 - 2000 MHz	>23 dB		

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

29/02/2016

Responsible

PierPaolo Piccinini

Description

Triple shielded coaxial cable for Broadband Distribution Networks
75 Ohm
Triple shielded cable (Screening Class A++)



Data Sheet

TS11J

2000 - 3000 MHz >20 dB

Screening Attenuation (SA)	SA-Class A++	Shield Transfer Impedance (Zt)	Zt-Class A+
30 - 1000 MHz	>110 dB	5 - 30 MHz	< 2 mOhm/m
1000 - 2000 MHz	>110 dB		
2000 - 3000 MHz	> 90 dB		


Attenuation (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	1,10	862	11,90
10	1,50	1000	12,80
30	2,20	1750	17,90
50	2,80	2150	19,80
200	5,60	2400	21,00
300	6,90	3000	24,50
470	8,80		

Attenuazione di schermatura / Screening Attenuation

Cavo classe A++ / A++ Class cable

Cavo tipo / Cable type : TS11J



Connectors

- FA17/73** Serie F Twist-On, F Twist-On, for indoor installation, nitin-plated brass - 33,0 mm x 14,5 mm
- F163** Series F Crimp, F Crimp, for indoor installation, nitin-plated brass - 35,0 mm x 14,0 mm
- FC11QM** Series F Compression, Quick Mount, for outdoor installation
- FM-32** Series F, male, for outdoor and underground installation, nitin-plated brass - 76,0 mm x 31,0 mm
- IEC14M-32** Series IEC (no tool), male, for outdoor and underground installation, nitin-plated brass - 64,5 mm x 21,0 mm

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

29/02/2016

Responsible

PierPaolo Piccinini

Description

Triple shielded coaxial cable for Broadband Distribution Networks
75 Ohm
Triple shielded cable (Screening Class A++)

**Data Sheet****TS11J****↑↑↑ Connectors**

- NM-32** Serie N, male, for outdoor and underground installation, nitin-plated brass - 62,5 mm x 21,0 mm
- 5/8MU-32** Serie 5/8", male, for outdoor and underground installation, nitin-plated brass - 69,0 mm x 20,5 mm
- 3,5/12M-32** Serie 3,5/12", male, for outdoor and underground installation, nitin-plated brass - 65,5 mm x 24,5 mm

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

29/02/2016

Responsible

PierPaolo Piccinini